



PSU-15-DIN30WC

15V - 30W Power supply unit for DIN rail mounting.

Key Features

- Low 56mm Profile
- Wide Range AC input
- Full Power at 61°C
- Fits into wall mounted cabinets
- Global use with no input selector switches
- No derating needed

Dimensions



Overview

The PSU-15-DIN30WC is a DINrail mounted power supply with a single fixed output rating of 30W at 15V.

Electrical Data

AC Input Voltage range: 90 - 264VAC,
Class II double insulated

Input Frequency: 47 - 63Hz

DC Input Voltage range: 120 - 370VDC

Inrush Current (115 / 230VAC): 25 / 50A

Output Voltage Accuracy %: $\pm 1\%$ of Nominal

Overcurrent Protection (Typ): 110 - 160%,
fold forward under short circuit

Overvoltage Protection V: 120 - 145%

LED Indicators: Green LED = On, Red LED = DC
Output Low

Operating Temperature: -25 to +71°C

Operating Humidity: 20 to 95% RH (non condensing)

Cooling: Convection

Immunity: EN61000-4-2, -3, -4, -5, -6, -8 & -11

Conducted & Radiated EMI: EN55022 class A



Contact your local Eaton office

T: +44 (0)1923 495495 F: +44 (0)1923 228796
E: enquiries@iLight.co.uk www.iLight.co.uk



Eaton Lighting Systems
20 Greenhill Crescent,
Watford Business Park,
Watford, Herts, WD18 8JA. UK
eatonlightingsystems.com

© 2019 Eaton
All Rights Reserved

Document No: PSU-15-DIN30WC Rev1 0919

Changes to the products, to
the information contained in
this document, and to prices
are reserved; so are errors and
omissions.

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.



FM 664349

